

according to regulation (EC) 1907/2006 (REACH) and regulation (EC) 2015/830

Trade name: CERACOAT ceramic Glass SC Sealing Version: 2.1 (last version: 2.0) page 1 of 7

Revision: 28.11.2022 Issue: 28.11.2022 print date: 01.09.2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Identification of the substance or mixture

CERACOAT ceramic Glass SC Sealing

1.2. Relevant identified uses of the substance or mixture and uses advised against relevant identified uses:

waterborne self-cleaning glass impregnation

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor)

CERACOAT Industries

Büfelderstrasse 1 Phone: +41 76 788 18 38

CH-8370 Sirnach

E-Mail info@ceracoat.me

Dept. responsible for information:

E-Mail (competent person) info@ceracoat.me

1.4. Emergency telephone number

Emergency Telephone of Company / Undertaking +41 76 788 18 38 (9am to 3 pm)

Counselling center for poisoning +49 (0)551 19240 (Giftnotrufzentrale GIZ Nord)

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture

Regulation (EC) No 1272/2008 This mixture is not classified as dangerous according to Regulation (EC) No 1272/2008.

2.2 Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures 1 percent of the mixture consists of one or more components of unknown acute toxicity.

For use in industrial plants only.

2.3 Other hazards

The ingredients of this product have been evaluated against the classification requirements for TiO2 as set out in the 14th ATP to Regulation (EU) 1272/2008 Annex VI. They do not meet the classification criteria.

SECTION 3. Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients:

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC-No	REACH-No	Wt% /
CAS-No	Chemical name	Remark
INDEX-No	Classification	
200-578-6	01-2119457610-43-0000	1 - < 5%
64-17-5	Ethanol	
603-002-00-	Flam. Lig. 2 H225	
5	•	

Hazardous ingredients

Additional information

Full text of classification: see section 16 (H- and EUH phrases)

CERACOAT Industries / Büfelderstrasse 1 / CH-8370 Sirnach / Switzerland Fon: +41 76 788 18 38 / E-Mail: info@ceracoat.me / Web: www.ceracoat.me / www.ceracoat.me



according to regulation (EC) 1907/2006 (REACH) and regulation (EC) 2015/830

Trade name: CERACOAT ceramic Glass SC Sealing Version: 2.1 (last version: 2.0) page 2 of 7

Revision: 28.11.2022 Issue: 28.11.2022 print date: 01.09.2023

SECTION 4. First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eve contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

Strong water jet.

5.2. Special hazards arising from the substance or mixture.

Provide a conveniently located respiratory protective device.

5.3. Advice for firefighters:

Provide a conveniently located respiratory protective device.

Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground, or waterways. Treat runoff as hazardous.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculite, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).



according to regulation (EC) 1907/2006 (REACH) and regulation (EC) 2015/830

Trade name: CERACOAT ceramic Glass SC Sealing Version: 2.1 (last version: 2.0) page 3 of 7

Revision: 28.11.2022 Issue: 28.11.2022 print date: 01.09.2023

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks, and open flames. Use only spark proof tools. Avoid contact with skin, eyes, and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink, or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

Conditions for safe storage, including any incompatibilities.

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use. Read label before use.

SECTION 8. Exposure controls / personal protection

Control parameters

Biological exposure limits (TRGS 903)

Additional information:

TWA: long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.



according to regulation (EC) 1907/2006 (REACH) and regulation (EC) 2015/830

Trade name: CERACOAT ceramic Glass SC Sealing Version: 2.1 (last version: 2.0) page 4 of 7

Hand protection

For prolonged or repeated handling, the following glove material must be used: nitrile rubber or butyl rubber with at least 0.7 mm thickness

Thickness of the glove material>= 0,7 mm

Breakthrough time (maximum wearing

time) > 480 min.

Observe the instructions and details for use, storage, maintenance, and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eve protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibres (cotton) or heat resistant synthetic fibres.

Protective measures

After contacting clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: liquid
Colour: translucent
Odour: none
Odour threshold: n.d.

Safety relevant basis data

Parameter	Value	Unit	Method	Remark
pH value	n.d.			
Melting point/range	n.d.	°C	ISO 3841	
Boiling point/range	n.a.	°C	ASTM D-1120	1013 hPa
Flash point	n.a.	°C	DIN 51755 Part 1	
Evaporation rate	n.d.			
Lower explosion limit	n.a.	Vol%		Solvent
Upper- explosion limit	n.a.	Vol%		Solvent
Vapour pressure at 20 °C	n.d.	hPa		
Density at 20 °C	0,98 - 1,02	g/cm³	DIN 51794	
Powder density	n.a.	Kg/m³		
solubility	Completely mixable with water	g/L		
Partition coefficient (n-	n.d.			
octanol/water)				
Thermal decomposition	n.d.			
Viscosity at 20 °C (dynamic)	n.d.	mPa·s		
Viscosity at 20 °C (kinematic)	n.d.	mm²/s		
Decomposition temperature	n.d.	°C		
Ignition temperature	n.d.			



according to regulation (EC) 1907/2006 (REACH) and regulation (EC) 2015/830

Trade name: CERACOAT ceramic Glass SC Sealing Version: 2.1 (last version: 2.0) page 5 of 7

n.a.: non-applicable n.d.: not determined

9.2. Other information

SECTION 10. Stability and reactivity

10.1. Reactivity

n.a.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition by-products may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11. Toxicological Information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

No data on preparation itself available.

Eye damage/irritation

slightly eye irritation

skin corrosion/irritation

Slightly skin irritation

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Carcinogenety, mutagenicity and toxicity for reproduction

_

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark:

There is no information available on the preparation itself.



according to regulation (EC) 1907/2006 (REACH) and regulation (EC) 2015/830

Trade name: CERACOAT ceramic Glass SC Sealing Version: 2.1 (last version: 2.0) page 6 of 7

SECTION 12. Ecological information

Overall evaluation

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP] There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

Water hazard class 1 - low hazard to waters (self-classification)

according to VwVwS (Verwaltungsvorschrift wassergefährdende Stoffe = German Administrative Regulation Regarding Water Pollutants).

Prevent from entering drains, ditches or rivers.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

Packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14. Transport information

No dangerous good in sense of this transport regulation

14.1. UN-number n.a.

14.2. UN proper shipping name

n.a.

14.3. Transport hazard class(es) n.a.

14.4. Packing group n.a.

14.5. Environmental hazards

Land transport (ADR/RID) n.a. Marine pollutant no

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 – 8

Additional information

Land transport (ADR/RID)

Tunnel restriction code

CERACOAT Industries / Büfelderstrasse 1 / CH-8370 Sirnach / Switzerland Fon: +41 76 788 18 38 / E-Mail: info@ceracoat.me / Web: www.ceracoat.me / www.ceracoat.me



according to regulation (EC) 1907/2006 (REACH) and regulation (EC) 2015/830

Trade name: CERACOAT ceramic Glass SC Sealing Version: 2.1 (last version: 2.0) page 7 of 7

Revision: 28.11.2022 Issue: 28.11.2022 print date: 01.09.2023

Sea transport (IMDG)

EmS-Nr. n.a.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

n.a.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Indications according to Directive 2004/42/EC

The VOC content of this product including the hardener component is < 4%

National legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

National regulations

Water hazard class: 1 – slightly hazard to waters (self-classification) according to VwVwS (Verwaltungsvorschrift wassergefährdende Stoffe = German Administrative Regulation Regarding Water Pollutants).

15.2. Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16. Other information

Full text of classification in section 3:

H225 Highly flammable liquid and vapor.

H318 Causes severe eye irritation.

Revised version:

_

Abbreviations and acronyms:

n.a. not available NB not determined

Additional information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP].

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in Chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.